



PLAN

GENERAL NOTES:

1. CONCRETE PAVING 100MM THICK FOR PEDESTRIAN FOOTPATH WITH BRUSHED FINISH.
2. AT SIGNALISED INTERSECTIONS PRAM RAMP POSITION TO CONFORM WITH AUSTRALIAN STANDARDS 1428.1 (2009).
3. TACTILES TO BE LAID THE WIDTH OF THE RAMP AND 800MM DEEP FOR PEDESTRIAN RAMPS.
4. TACTILES TO BE LAID MINIMUM 300MM FROM EDGE OF ROAD.
5. ALL TACTILE GROUND SURFACE INDICATORS (PAVERS) SHALL COMPLY WITH AS1428.4.1 2009 CLAUSE 2.2 & 2.3.
6. RAMPS ARE TO MATCH THE SURROUNDING IN COLOUR AND TEXTURE. CONCRETE MIX 32MPA. MIX NEEDS TO BE WASHED TO PRODUCE A WASHED AGGREGATE FINISH.
7. ALL TRANSVERSE EXPANSION JOINTS SHALL BE "ALL-IN ONE LOCK" & EXPANSION JOINT OR EQUIVALENT AT MAX SPACING OF 6M.
3. ALL LONGITUDINAL EXPANSION JOINTS SHALL BE 75MM X 10MM 'ABELFLEX', BUTYL MASTIC SEALANT (COLOUR: GREY) TO BE USED ON EXPANSION JOINTS WITH 'PAVELOCK' SAND OR SIMILAR APPROVED.